

DESCRIPTION

Alkathene WNC199 is an extrusion coating grade exhibiting very low odour and taint and excellent heat seal characteristics. It also has good drawdown allowing low coating weights whilst maintaining very good adhesion to a variety of substances.

APPLICATION

Alkathene WNC199 is ideally suited for liquid packaging and other sensitive food packaging laminates.

FOOD CONTACT / PRODUCT SAFETY

For food contact information please refer to the Regulatory Data Sheet at genos.com. For product safety information please refer to the Safety Data Sheet at genos.com.

Polymer Properties	Value ¹	Units	Test Method
Melt Index @ 190°C, 2.16 kg	8.0	g/10 min	ASTM D1238
Density	0.918	g/cm ³	ASTM D1505
Melting Temperature	106	°C	ASTM D3418
Vicat Softening Temperature	86	°C	ASTM D1525

1. Typical values - not to be construed as specifications.

For up to date information, refer to genos.com

This information is offered solely for your consideration, investigation, verification and shall not be construed as a warranty or representation for which Qenos Pty Ltd assumes legal liability, except to the extent that such liability is imposed by legislation and cannot be excluded. Values quoted are the result of tests on representative samples, and the product supplied may not conform in all respects. Qenos Pty Ltd reserves the right to make any improvements or amendments to the composition of any grade or product without alteration to the code number. In using Qenos Pty Ltd's products, you must establish for yourself the most suitable formulation, production method and control tests, to ensure the uniformity and quality of your product in compliance with all laws. Qenos Pty Ltd ACN 054 196 771 is the registered user of the Qenos Logo which is registered trademark of Qenos Pty Ltd. "Alkathene" is a trademark of Qenos Pty Ltd.